



Pos.	P/N	Description	Q.ty	K1	K2	K3	K4	Pos.	P/N	Description	Q.ty	K1	K2	K3	K4
1	30.5817.24	Casing-kit -RL600 + screws, Sst.	1				1	15	30.5805.55R	Housing -RL600, Sst.	1				3
2	16.3075.51R	S/tapping scr. 3,5x18 mm sst.	7				10	16	10.3059.01R	O-ring, 1,78x11,11 mm Ni 85	1	•			10
3	30.5815.84R	Plug, 1/4M Bsp DIN259 Plast. black	1				10	17	10.4036.00R	Back-up ring, 11,7x14,5x2 mm	1	•			10
4	30.5809.51R	Spring coupl., 1/4F Bsp-M22x1M Sst.	1				5	18	30.5803.51R	Front body, 3/8F Bsp Sst.	1				3
5	10.4037.00R	Back-up ring, 16,7x19,5x2 mm	1	•			10	19	30.5808.51R	Front Plug, M14x1 Sst.	1				5
6	10.3066.01R	O-ring, 1,78x15,6 mm Ni 85	1	•			10	20	30.5813.31R	Parallel pin, 6x20 mm brass	1				3
7	10.2006.00R	Stem seal, 6x11x2,2 mm +O-ring	2	•			10	21	30.0675.51R	Stop pin, 8x7,1mm Sst.	1				10
8	30.5812.51R	Spacer ring, Sst.	1	•			5	22	30.2517.31R	Parallel pin, 5x27,5 mm brass	1				10
9	30.5810.51R	Spring, 2,2x12x27 mm Sst.	1	•			5	23	30.1510.84R	Safety latch, PA red	1				10
10	30.5816.24	Piston+Seat -RL600, 2x1pcs.	1	•			1	24	30.5804.84R	Trigger -RL600, PA black	1				5
11	10.3064.01R	O-ring, 1,78x14 mm Ni 85	1	•			10	25	30.5821.51R	Magnet, 5x8 mm (1)	1				5
12	10.4038.00R	Back-up ring, 15,2x18x2 mm	1	•			10	26	12.5003.00R	Probe with cable 2000 mm (1)	1				5
13	30.5807.51R	Coupl., M16x1,5F-G3/8F Sst.	1				3	27	30.5060.00	Shoulder rest -RL600 1/4M Bsp 300mm **	1				1
14	30.5806.56R	Tube, M16x1,5 FF 135mm Sst.	1				5								

\*\* On request

Kit	P/N	Description	Q.ty
K1	30.5819.24	Spares kit -RL600, 10(11)x1pcs.	1

(1) 30.5820.00